



## JET COX GLASSLIGHT

The JET COX Glasslight is an innovative flat glass rooflight solution suitable for all flat roof applications.

Manufactured from thermally broken durable aluminium with an external powder coating finish to RAL 9040, it is one of the most attractive flat glass solutions on the market. The glass surface is uninterrupted giving optimal view and maximum daylight. The Glasslight is available fixed or electrically opening for ventilation. The electric actuator is fully integrated and concealed within the PVC-u lower frame and allows the rooflight to open for ventilation to approximately 350mm.

The Glasslight, not only aesthetically pleasing, also offers superb performance.

Please note: The Glasslight is also available without the upstand for direct installation onto an existing builder's kerb / upstand. Contact our Sales Office for further information and advice on kerb sizing.



### TECHNICAL SPECIFICATION

- **'U' Value** 1.2 W/m<sup>2</sup>K (with upstand)  
1.6 W/m<sup>2</sup>K (without upstand)
- **Light Transmission** 79%
- **'G' Value (Solar Gain)** 63%
- **Sound Reduction according to NEN-EN-5079**  
36dB - 39dB
- **Wind Load according to NEN-EN6702:2001**  
– 0.8kN/m<sup>2</sup>
- **Safety Glass according to NEN-EN-3569 / 12600**
- **External Finish RAL 9040 / Internal Finish RAL 9010**
- **Minimal 3° Pitch (shortest side)**
- **RO16 PVC-u Upstand**

Designed to be a feature, not just to provide a function!

Rooflight Size	Fixed on Upstand	Electric on upstand	Fixed without Upstand	Electric without Upstand
400 x 700	•	•	•	•
600 x 600	•	•	•	•
600 x 900	•	•	•	•
600 x 1800	•	•		
600 x 2400	•	•		
700 x 700	•	•	•	•
700 x 1000	•	•	•	•
800 x 800	•	•	•	•
800 x 1300	•	•	•	•
800 x 1800	•	•		
800 x 2400	•	•		
900 x 900	•	•	•	•
1000 x 1000	•	•	•	•
1000 x 1800	•	•		
1000 x 2400	•	•		
1200 x 1200	•	•	•	•