


## COXDOME GALAXY RANGE

The 'dome-only' solution for the refurbishment and replacement of rooflights fitted to existing kerbs and upstands

- Designed to be fitted to existing builder's kerbs
- 100mm flanged polycarbonate unit, ensures a fit with most kerbs without the need for adjustment
- Ideal for refurbishments where only glazing needs to be replaced
- Class 1 fire performance to BS476 Pt7
- Suitable for installation on a roof pitch between  $0^\circ$  and  $15^\circ$

All sizes available in single, double, triple and quadruple skin.

## **Clear or diffused glazing options**



Minimum 50mm builder's kerb required, ideally 100mm maximum.

## **IMPORTANT NOTE:**

The glazing tape between the polycarbonate layers is 100mm and therefore can be visible on builder's kerbs of less than 100mm width.

## All Galaxy domes are supplied with fixings, and undrilled for maximum flexibility.



Pyramids, trapezoids and circular domes are not available in the Galaxy range.



- In triple skin format, Galaxy has a U-value of 1.7W/m2K
- Manufactured using 3mm polycarbonate which achieves B-s1-d0 and therefore attains Class 1 certification (according to EN 13501-1:2007)
- Class B non-fragile to ACR[M]001

Nominal Size Chart	Min Ext Kerb	Actual Rooflight Size
600 x 600	510 x 510	640 x 640
600 x 900	510 x 810	640 x 940
600 x 1200	510 x 1120	640 x 1250
600 x 1800	510 x 1730	640 x 1860
750 x 750	660 x 660	790 x 790
750 x 900	660 x 810	790 x 940
900 x 900	810 x 810	940 x 940
900 x 1200	810 x 1120	940 x 1250
900 x 1800	810 x 1730	940 x 1860
1050 x 1050	970 x 970	1100 x 1100
1050 x 1500	970 x 1420	1100 x 1550
1200 x 1200	1120 x 1120	1250 x 1250
1200 x 1800	1120 x 1730	1250 x 1860
1200 x 2400	1120 x 2340	1250 x 2470
1500 x 1500	1420 x 1420	1550 x 1550
1800 x 1800	1730 x 1730	1860 x 1860

COXDOME is a UK manufacturer, providing natural daylight and ventilation solutions since 1954

